

COAXIAL ANTENNA
TYPE:

 RFX 1 1/4"-50
 RFX 1 1/4"-50 GHF
 RFX 1 1/4"-50 BHF

NK CODE:

 NKRFX11400
 NKRFX11401
 NKRFX11402

CONSTRUCTION


Inner conductor	Copper tube	Ø 13.0 mm	(0.51 in)
Dielectric	Cellular polyethylene	Ø 32.2 mm	(1.27 in)
Outer conductor	Corrugated single side slotted copper tube	Ø 35.8 mm	(1.41 in)
Jacket	See Jacketing Options table below	Ø 39.0 mm	(1.54 in)
Marking	NK Cables, cable type, manufacture week, year, batch number and meter mark		

ELECTRICAL CHARACTERISTICS at +20°C (+68°F)

Characteristic impedance		50 ± 2 Ω	
Typical return loss (VSWR) on effective frequency range		18 dB	(1.29)
Velocity factor		0.88	
Capacitance		75 pF/m	(23 pF/ft)
Maximum frequency		3500 MHz	
DC-resistance			
- Inner conductor		0.74 Ω/km	(0.22 Ω/1000 ft)
- Outer conductor		0.65 Ω/km	(0.20 Ω/1000 ft)
Attenuation (measured acc. to IEC 61196-4 free space method)			
at 75 MHz	1.0 dB/100m		(0.31 dB/100ft)
at 150 "	1.3 "		(0.40 ")
at 450 "	2.2 "		(0.67 ")
at 900 "	3.2 "		(0.98 ")
at 1.8 GHz	4.9 "		(1.50 ")
at 2.2 "	5.6 "		(1.71 ")
at 2.4 "	6.2 "		(1.89 ")
Coupling loss (measured acc. to IEC 61196-4 free space method)			
	<u>50% value</u>	<u>95% value</u>	
at 75 MHz	62 dB	68 dB	
at 150 "	68 "	73 "	
at 450 "	70 "	76 "	
at 900 "	71 "	78 "	
at 1.8 GHz	75 "	80 "	
at 2.2 "	76 "	81 "	
at 2.4 "	79 "	86 "	

MECHANICAL CHARACTERISTICS

Weight	0.89 kg/m	(0.60 lb/ft)
Maximum pulling force	6050 N	(1340 lb)
Minimum single bending radius	350 mm	(14 in)
Operating temperature range	-55...+80°C	(-67...+176 °F)

JACKETING OPTIONS

TYPE	JACKET	IEC 60754 -1/-2 halogen free, non corrosive	IEC 61034 low smoke emission	IEC 60332-1 fire retardant	UV retardancy	Min. installation temperature
RFX 1 1/4"-50	Black, halogen free polyethylene	yes	no	no	yes	-40°C (-40°F)
RFX 1 1/4"-50 GHF	Grey, halogen free fire retardant thermoplastic	yes	yes	yes	no	-5°C (-4°F)
RFX 1 1/4"-50 BHF	Black, halogen free fire retardant thermoplastic	yes	yes	yes	yes	-5°C (-4°F)