



**Mechanical characteristics**  
cables

**Mechanische Eigenschaften**  
Kabel

G 7: KX 22A; KX 3B; RG-174/U;  
MRC 100 Flex (0.48L/1.5AF) Draka;  
RG-188A/U; RG-316/U  
RG-179B/U, RG-187A/U

assembly code  
panel piercing

Montageanleitung  
Montagebohrung

D06  
Z041

**Components**  
body

**Bauteile**  
Körper

**Materials / Material**  
CuZn39Pb3

**Finish / Oberfläche**  
Cu1-2Ni-2Sn3-6 matt

**Electrical characteristics**  
impedance

**Elektrische Eigenschaften**  
Wellenwiderstand

50 Ω

**Environmental**  
RoHS compliant

**Umgebung**  
RoHS konform

2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	06.11.2019	MA		
			gepr./ appr.	06.11.2019	BJ	ca./approx. 0,23	
			Maßstab/ scale 10:1 (1:1)	Benennung/ title Cable Terminator for PCB Kabeldirektanschluss für LTP			
			unt. Maß/ dim. without tolerances according to	Untert./ doc. type K	Zeichnungsnr./ drawing no. H01000A0247		
			Ersatz für/ replaces				 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1