

RFA 7/8" L A LIGHT COAXIAL COPPER CABLE

RFA 7/8" -50 L BHF Dca

 Material code
 60069209

 Dop
 1007235

CONSTRUCTION


Inner conductor	Copper tube	Ø 9.0 mm	(0.35 in)
Dielectric	Cellular polyethylene	Ø 22.2 mm	(0.87 in)
Outer conductor	Corrugated copper tube	Ø 24.9 mm	(0.98 in)
Jacket	See Jacketing Options table below	Ø 27.5 mm	(1.08 in)
Marking	Draka, cable type, CPR class, manufacture week/year, batch number and meter mark		

ELECTRICAL CHARACTERISTICS at +20°C (+68°F)

Characteristic impedance	50 ± 1 Ω
Min. Return loss with delivery lengths	
790 – 960 MHz	20 dB
1710 – 1880 MHz	20 dB
1900 – 2170 MHz	20 dB
2490 – 2700 MHz	20 dB
3400 – 3800 MHz	20 dB
Other bands also available on request	
RL typically 24 dB for 100 m cable with NKC connectors	
Attenuation	See table
Velocity factor	0.88
Capacitance	76.0 pF/m (23 pF/ft)
Inductance	0.190 µH/m (0.945 µH/ft)
Maximum frequency	5100 MHz
Max power rating	See table
Peak RF voltage rating	3.1 kV
Peak power rating	95 kW
DC-resistance	
Inner conductor	2.02 Ω/km (0.62 Ω/1000 ft)
Outer conductor	1.51 Ω/km (0.46 Ω/1000 ft)

MECHANICAL CHARACTERISTICS

Weight (BHF fire retardant jacket)	0.46 kg/m	(0.31 lb/ft)
Maximum pulling force	2000 N	(450 lb)
Minimum bending radius		
Single bending	120 mm	(5 in)
Repeated bending	240 mm	(9 in)
Operating temperature range	-55...+85°C	(-67...+185°F)
Crush resistance	1.45 kg/mm	(81 lb/in)
Bending moment	13 Nm	(10 lb-ft)
Recommended clamp spacing	1.0 m	(3.3 ft)

JACKETING OPTIONS

TYPE	JACKET	IEC 60754 -1/-2 Halogen free, non corrosive	IEC 61034 low smoke emission	IEC 60332-3-24 fire retardant	CPR class	UV retardancy	Min. installation temperature
RFA 7/8" -50 L BHF Dca	Black, halogen free fire retardant thermoplastic	yes	yes	yes	Dca-s2d2a2	yes	-20°C (-4°F)

CONNECTOR CODES

NKC1078300 N male
 NKC1078400 N female
 NKC1078100 7/16 male
 NKC1078200 7/16 female
 NKC1078500 7/16 male Right angle
 NKC1078700 4.3/10 female
 NKC1078P00 4.3/10 male (screw)
 NKC1078290 7/16 Bulkhead female

ACCESSORIES & TOOLS & INSTALLATION

Knife and hacksaw can be used as connector installation tools.

Please contact your salesperson if any further questions.

RFA 7/8" L COAXIAL CABLE

FREQUENCY MHz	ATTENUATION dB/100 m	POWER RATING kW	FREQUENCY MHz	ATTENUATION dB/100 m	POWER RATING kW
0.5	0.080	95	900	3.7	2.47
1.0	0.113	83	925	3.8	2.43
1.5	0.138	68	950	3.8	2.40
1.85	0.153	61	960	3.9	2.38
2.0	0.160	59	1000	4.0	2.33
3.7	0.217	43	1250	4.5	2.06
5.3	0.261	35.9	1400	4.8	1.93
7.1	0.302	30.9	1500	5.0	1.86
10	0.36	26.0	1575	5.1	1.81
14	0.43	21.9	1700	5.3	1.73
18	0.48	19.3	1800	5.5	1.68
20	0.51	18.3	1900	5.7	1.62
25	0.57	16.3	2000	5.8	1.58
28	0.61	15.4	2100	6.0	1.53
30	0.63	14.8	2200	6.2	1.49
50	0.81	11.4	2400	6.5	1.41
70	0.97	9.6	2500	6.6	1.38
75	1.00	9.3	2600	6.8	1.35
88	1.09	8.5	2700	6.9	1.32
100	1.16	8.0	2800	7.1	1.29
108	1.21	7.7	3000	7.4	1.24
144	1.41	6.6	3400	7.9	1.15
150	1.44	6.5	3500	8.1	1.14
174	1.55	6.0	3600	8.2	1.12
200	1.67	5.6	3700	8.3	1.10
220	1.76	5.3	3800	8.5	1.08
300	2.07	4.5	4000	9	1.05
380	2.34	4.0	4900	10	0.93
400	2.41	3.9	5000	10	0.92
432	2.51	3.7	5100	10	0.91
450	2.57	3.61			
500	2.71	3.42			
512	2.75	3.37			
600	2.99	3.08			
700	3.26	2.83			
750	3.38	2.73			
800	3.50	2.63			
824	3.56	2.59			
870	3.67	2.52			
890	3.71	2.48			
894	3.72	2.48			

Attenuation at imperial scale can be calculated: [dB / 100 m] * 0.3048 = [dB / 100 ft].

Attenuation values are typical at ambient temperature +20°C (+68°F).

Power rating ambient temperature +40°C (+104°F), inner conductor +100°C (+212°F).

© PRYSMIAN GROUP 2022, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.