

**Mechanical characteristics**

cables

interface dimensions acc. to assembly code

center conductor  
outer conductor

mating life

**Components**

center contact  
outer contact  
bayonet  
springwasher  
other metal parts  
insulator  
gasket

**Electrical characteristics**

impedance  
frequency  
working voltage  
voltage proof  
insulation resistance  
contact resistance  
center contact  
outer contact

**Environmental**

operating temp.  
RoHS compliant

**Mechanische Eigenschaften**

Kabel

Steckgesicht nach Montageanleitung

Innenleiter  
Außenleiter

Steckzyklen

**Bauteile**

Innenkontakt  
Außenkontakt  
Bayonett  
Federscheibe  
sonstige Metallteile  
Isolierung  
Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Betriebsspannung  
Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**

Betriebstemperatur  
RoHS konform

**only for cable with solid inner conductor / nur für Kabel mit massivem Innenleiter**

Ⓐ 2.7/7.3 AF, 2.7/7.3 CF, 213CRT7 Low Loss, 7810A, 9913, Aircom Premim, C2FCP, C2FP, CNT-400, EC 400, HPF 400, LMR-400, MRC 400 AFB, SPEEDFOAM 400 HFJ, TZC 500 32, WBC-400, WCX400, 02Y(St) C (St) H, 2.6/7.3 AF, 213RT5, 9914, H 1000, H 2000, RT 50/20  
IEC 61169-8  
B87  
clamp / klemm  
clamp / klemm  
>500



**Materials / Material**

copper alloy/Kupferleg.  
brass/Messing  
zinc diecast/Zinkdruckguss  
copper alloy/Kupferleg.  
brass/Messing  
PTFE  
NBR

**Finish / Oberfläche**

NiP Au  
Cu2Ni5  
Zn/Cu6Ni6  
Cu2Ni5  
Cu2Ni5/CuSnZn

50 Ω  
0-4 GHz  
≤ 500V<sub>eff</sub> / 50 Hz  
1,5 kV<sub>eff</sub> / 50Hz  
≥ 5 GΩ  
≤ 20 mΩ  
≤ 5 mΩ  
-30°C / +85°C  
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	08.12.2016	BJ	
			gepr./ appr.	15.12.2016	KL	ca./approx. 46
			Maßstab/ scale	Benennung/ title		
			2:1	Ⓐ BNC Straight Plug, field mount type BNC-Kabelstecker, Feldmontage-Type		
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
				K	J01000A0072	
a	29732	05.07.2018	MA	Ersatz für/ replaces		