

**Mechanical characteristics**  
cable group

**Mechanische Eigenschaften**  
Kabelgruppe

G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V;  
 75022 V(0.6L/3.7) Sytronic Kabel GmbH;  
 75060 V(0.6/3.7) Sytronic Kabel GmbH;  
 8241 Belden; KX 6A; RG-59B/U;  
 VK95 0.6/3.7 Percon

interface dimensions acc. to  
 assembly code  
 centre conductor  
 outer conductor  
 mating life

Steckgesicht nach  
 Montageanleitung  
 Innenleiter  
 Außenleiter  
 Steckzyklen

IEC 61169-8  
 A0831  
 crimp  
 crimp  
 >500

**Components**  
 centre contact  
 outer contact  
 crimp ferrule  
 insulator

**Bauteile**  
 Innenkontakt  
 Außenkontakt  
 Crimprohr  
 Isolierung

**Materials / Material Finish / Oberfläche**  
 CuPb1.15Ni1 (C97) NiP-Au  
 CuZn39Pb3 Cu2Ni5  
 Cu SF w Ni5  
 PE-LD

**Electrical characteristics**

**Elektrische Eigenschaften**

impedance  
 frequency  
 working voltage  
 insulation resistance  
 contact resistance  
 centre contact  
 outer contact


Wellenwiderstand  
 Frequenz  
 Betriebsspannung  
 Isolationswiderstand  
 Durchgangswiderstand  
 Innenkontakt  
 Außenkontakt

75 Ω  
 0-4 GHz  
 ≤ 500 kV<sub>eff</sub> / 50 MHz  
 ≥ 5 MΩ  
 ≤ 20 mΩ  
 ≤ 5 mΩ

**Environmental**  
 operating temp.  
 RoHS compliant

**Umgebung**  
 Betriebstemperatur  
 RoHS konform

-30°C / +75°C  
 2011/65/EU



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	19.10.2016	MA		
			gepr./ appr.	21.11.2016	KL	ca./approx. 11	
Maßstab/ scale 2:1 (1:1)		Benennung/ title BNC Straight Jack BNC-Kabelbuchse					
untol. Maße/ dim. without tolerances according to		Untert./ doc. type K	Zeichnungsnr./ drawing no. J01003A1369				
Ersatz für/ replaces						Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1	